### Halsey Taylor<sub>®</sub> WaterSentry<sup>®</sup> Plus Lead, Chlorine, Taste & Odor, and Particulate Class I Reduction Filter Part No. 55898C FOR HWF3000 - WaterSentry<sup>®</sup> Plus *FOR COMMERCIAL USE ONLY* **PERFORMANCE DATA SHEET**



The WaterSentry<sup>®</sup> Plus filter is tested and certified by NSF International to NSF/ANSI 42 and 53 for the reduction of Chlorine, Taste and Odor, Particulate Class I, and Lead.

IMPORTANT NOTICE: Read this Performance Data Sheet and compare the capabilities of this unit with your actual water treatment needs. It is recommended that, before purchasing a water treatment unit, you have your water supply tested to determine your actual water treatment needs.

NOTICE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

CAUTION: Use on cold water line only. Do not allow installed filter to freeze.

RECOMMENDED USE CONDITIONS						
Capacity	3000 Gallons 1 Year Maximum	Maximum Pressure	105 PSI (7.4 Kg/cm <sup>2</sup> )			
Flow Rate	1.5 GPM					
Temperature	40-100° F (5-38° C)	Minimum Pressure	20 PSI (1.4 Kg/cm <sup>2</sup> )			

- NOTE: Performance will vary depending on local water conditions. While testing was performed under standard laboratory conditions actual performance may vary.
- NOTE: This system and installation shall comply with applicable state and local regulations.

NOTE: Filter must be used with filter monitor for 3000 gallon rating.

# Instructions For Installing Replacement Filters

# *To avoid danger of an electric shock hazard, disconnect power to your unit before installing or replacing the filter.*

- 1. Turn off water supply; dispense water to relieve pressure
- 2. Turn used filter counterclockwise 1/4 turn to remove from filter head.
- 3. Remove cap from new filter and use to seal used filter.
- 4. Insert new filter into existing filter head and turn fully clockwise.
- Turn on water supply and run a minimum of two gallons of water through the filter to purge air and fine carbon particles from filter. Also run water through glass filler (if provided).

## LIMITED WARRANTY

The Halsey Taylor<sub>®</sub> WATERSENTRY<sup>®</sup> Plus is warranted to be free from defects in material and workmanship for a period of one year from the date of installation. Warranty is limited to repair or replacement of defective component.

Your Authorized Representative
Buyer
Seller

98524C (Rev. SIH - 06/19)

[ <u></u>		Performance	ce Test Conditions
NSF/ANSI 42	NSF/ANSI 53	Capacity	3000 Gallons (11356 I)
Chlorine Reduction Particulate Class I Reduction	Lead Reduction	Flow Rate	1.5 gpm (2.8 l/m)
Taste and Odor Reduction		Pressure	60 psi (4.2 kg/cm <sup>2</sup> )
		Temperature	68-70° F (20-21° C)

This system has been tested according to NSF/ANSI 42 and 53 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42 and 53.

#### Table 1 Lead Reduction

Contaminant	Average Average Influent Effluent		Average % Reduction / Minimum % Reduction	Maximum Effluent	Influent Challenge Concentration	Max. Permissible Product Water Concentration
Lead (pH 6.5)	.150 mg/l	0.003 mg/l	98.9% / 94.1%	0.009 mg/l	.15 ± 10% mg/l	.010 mg/l
Lead (pH 8.5)	.142 mg/l	<0.0005 mg/l	>99.6% / >99.6%	<0.0005 mg/l	.15 ± 10% mg/l	.010 mg/l

Average concentrations are the arithmetic mean of all reported influent or effluent concentrations (The detection limit value shall be used for any non-detectable concentrations.) The percent reduction shall be calculated from the arithmetic mean of the influent and effluent concentrations.

#### Table 2 Aesthetic Chlorine Reduction

· · ·	Ŭ	Maximum Effluent		Minimum % Reduction	Influent Challenge Concentration	Reduction Requirement
1.97 mg/l	.02 mg/l	.02 mg/l	mg/l	99.0	2.0 mg/l ±10%	≥50%

Table 3 Particulate Class I Reduction (Particle Size: 0.5 - 1 micron)

•	Average Effluent	Maximum Effluent		Minimum % Reduction	Influent Challenge Concentration	Reduction Requirement
76,613	183	405	particles/ml	99.5	min. 10,000 particles/ml	≥85%

Halsey Taylor

2222 CAMDEN COURT OAK BROOK, IL 60523 630.574.3500

PRINTED IN U.S.A.

FOR REPLACEMENT FILTER, PLEASE CALL 1.630.574.3500

98524C (Rev. SIH - 06/19)

PAGE 2