Architectural/Engineering Specification:

Polished chrome plated 4"[102mm] centerset single control lavatory faucet with 5" [127mm] integral spout, a ceramic disc cartridge and a temperature limit stop. Installed with the unit is a 2.2 GPM [8.3L] aerator (complying with ANSI A112.18.1M Standard for flow), an ADA compliant lever handle, and a 3/8" stainless steel flex hose 18" [457mm] in length with a 3/8" female compression fitting.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

Model	Lever	No	With	With	With
No.	Handle	Pop-Up	Lift Rod	Metal	Grid
		Hole	Only	Pop-Up	Strainer
Z7440-XL	Х	Х			
Z7441-XL	Х		Х		
Z7442-XL	Х			Х	
Z7443-XL	Х	Х			Х

STANDARDS

Lever handle models meet or exceed ANSI A117.1M Handicap specifications.

FLOW RATE

2.2 GPM (8.3 LPM) @ 80 PSI

Compliance and Certification:

- Low-Lead Compliant
- ADA Compliant



*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



Aerator Options:

	Flowrate GPM [LpM]	Vandal Resistant	*WaterSense Labeled	Outlet Type
-FC	0.5[1.9]	✓		Aerator
-LA	2.2[8.3]	✓		Laminar
-80	1.0[3.8]		✓	Spray
-VP	2.2[8.3]	✓		Aerator
-VP1.5	1.5[5.7]	√	✓	Spray
-SO.35	0.35[1.3]			Laminar
-SOVP.35	0.35[1.3]	√		Spray

Suffix Options:

-CST Copper Supply Tubes w/ 1/2" IPS Fitting

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



US 1.855.ONE.ZURN CANADA 1.905.405.8272 ZURN.COM



Sierra Faucet

Rough-in/Overview dimensions





